

PVC-INSULATED PIN TERMINALS (EASY ENTRY)



ITEM NO	DIMENSIONS inch (mm)				WIRE RANGE A.W.G. mm ²
	BRAZED SEAM	D	B	F	
ITFT-VEP1.25-9B	0.150(3.80)	0.079(2.00)	0.354(9.00)	0.030(0.75)	22-16 A.W.G. 0.5-1.5 mm ²
ITFT-VEP2-10B	0.169(4.30)		0.394(10.00)	0.031(0.80)	16-14 A.W.G. 1.5-2.5 mm ²
ITFT-VEP5.5B	0.228(5.80)	0.106(2.70)	0.535(13.60)	0.039(1.00)	12-10 A.W.G. 4-6 mm ²

ITEM NO	DIMENSIONS inch (mm)				WIRE RANGE A.W.G. mm ²
	BUTTED SEAM	D	B	F	
ITFT-VEP1.25	0.150(3.80)	0.079(2.00)	0.472(12.00)	0.030(0.75)	22-16 A.W.G. 0.5-1.5 mm ²
ITFT-VEP2	0.169(4.30)		0.472(12.00)	0.031(0.80)	16-14 A.W.G. 1.5-2.5 mm ²
ITFT-VEP5.5	0.228(5.80)	0.106(2.70)	0.535(13.60)	0.039(1.00)	12-10 A.W.G. 4-6 mm ²

Packaging: 100 pcs per packet

Features

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.